










Modèle Configuration	Nombre de brins	Angle	 Modèle 18-08				
			4t	6,7t	10t	31,5t	50t *
CMU			4t	6,7t	10t	31,5t	50t *
Epaisseur de la soudure			HY 4 + a 3	HY 5 + a 3	HY 8 + a 3	HY 17	HY 25
	1	0°	4	6,7	10	31,5	50
	2	0°	8	13,4	20	63	100
	1	90°	4	6,7	10	31,5	50
	2	90°	8	13,4	20	63	100
	2	A 0°-45°	5,6	9,4	14	44,1	70
		A 45°-60°	4	6,7	10	31,5	50
	2	Asymétrique	4	6,7	10	31,5	50
	3-4	A 0°-45°	8,4	14,1	21	66,2	105
		A 45°-60°	6	10,1	15	47,3	75
	3-4	Asymétrique	4	6,7	10	31,5	50

A° maximum : 60° / B° minimum : 30°.

Charge maximale exprimée en Tonne.

* Sans paliers.

EMILE MAURIN

7 Chemin de la Pierre Blanche

69800 SAINT PRIEST

Fax 04.72.76.22.55

composants.emile-maurin.fr



0 825 007 888

Service 0,15 € / min
+ prix appel



Demande de renseignement

Toutes nos actualités