








Anneau de levage articulé à paliers, à souder

Modèle	Nombre de brins	Angle	 Modèle 18-08						
Configuration									
CMU			4t	6,7t	10t	16t	31,5t	50t	100t
Epaisseur de la soudure			HY 3	HY 5	HY 6	HY 9	HY 12	HY 19	HY 28
	1	0°	4	6,7	10	16	31,5	50	100
	2	0°	8	13,4	20	32	63	100	200
	1	90°	4	6,7	10	16	31,5	50	100
	2	90°	8	13,4	20	32	63	100	200
	2	A 0°-45°	5,6	9,4	14	22,4	44,1	70	140
		A 45°-60°	4	6,7	10	16	31,5	50	100
	2	Asymétrique	4	6,7	10	16	31,5	50	100
	3-4	A 0°-45°	8,4	14,1	21	33,6	66,2	105	210
		A 45°-60°	6	10,1	15	24	47,3	75	150
	3-4	Asymétrique	4	6,7	10	16	31,5	50	100

A° maximum : 60° / B° minimum : 30°.
Charge maximale exprimée en Tonne.

EMILE MAURIN

7 Chemin de la Pierre Blanche

69800 SAINT PRIEST

Fax 04.72.76.22.55

composants.emile-maurin.fr



0 825 007 888

Service 0,15 € / min
+ prix appel

Demande de renseignement

Toutes nos actualités