










Modèle Configuration	Nombre de brins	Angle	 Modèle 18-152						
			1,5t	2,5t	4t	6,7t	10t	16t	20t
CMU			1,5t	2,5t	4t	6,7t	10t	16t	20t
Epaisseur de la soudure			a 4	a 5	a 6	a 6	a 8	a 8	a 8
	1	0°	1,5	2,5	4	6,7	-	-	-
	2	0°	3	5	8	13,4	-	-	-
	1	90°	1,5	2,5	4	6,7	10	16	20
	2	90°	3	5	8	13,4	20	32	40
	2	A 0°-45°	2,1	3,5	5,6	9,4	14	22,4	28
		A 45°-60°	1,5	2,5	4	6,7	10	16	20
	2	Asymétrique	1,5	2,5	4	6,7	10	16	20
	3-4	A 0°-45°	3,15	5,25	8,4	14,1	21	33,6	42
		A 45°-60°	2,25	3,75	6	10	15	24	30
	3-4	Asymétrique	1,5	2,5	4	6,7	10	16	20

A° maximum : 60° / B° minimum : 30°.

Charge maximale exprimée en Tonne.

ATTENTION : - CMU 1,5 à 6,7T: Amplitude de traction 150°. Amplitude de traction latérale +45° à -45°.

- CMU 10 à 20T: Amplitude de traction 45°. Amplitude de traction latérale +15° à -15°.

→ Cf schéma sur la fiche produit.

EMILE MAURIN

7 Chemin de la Pierre Blanche

69800 SAINT PRIEST

Fax 04.72.76.22.55

composants.emile-maurin.fr



0 825 007 888

Service 0,15 € / min
+ prix appel



Demande de renseignement

Toutes nos actualités