








Modèle	Nombre de brins	Angle	 Modèle 18-19						
Configuration									
CMU			0,8t	1,6t	3,2t	5t	10t	20t	31,5t
Epaisseur de la soudure			a 3	a 4	a 6	a 7	a 8	a 12	a 15
	1	0°	0,8	4	9	12	20	20	31,5
	2	0°	1,6	8	18	24	40	40	63
	1	90°	0,8	1,6	3,2	5	10	20	31,5
	2	90°	1,6	3,2	6,4	10	20	40	63
	2	A 0°-45°	1,1	5,6	12,6	16,8	28	28	45
		A 45°-60°	0,8	4	9	12	20	20	31,5
	2	Asymétrique	0,8	4	9	12	20	20	31,5
	3-4	A 0°-45°	1,7	3,4	6,8	10,6	21,2	42	67
		A 45°-60°	1,2	2,4	4,8	7,5	15	30	47,5
	3-4	Asymétrique	0,8	1,6	3,2	5	10	20	31,5

A° maximum : 60° / B° minimum : 30°.
Charge maximale exprimée en Tonne.

EMILE MAURIN

7 Chemin de la Pierre Blanche

69800 SAINT PRIEST

Fax 04.72.76.22.55

composants.emile-maurin.fr



0 825 007 888

Service 0,15 € / min
+ prix appel



Demande de renseignement

Toutes nos actualités